Stylelint CSS linter

CONCEPTS

> Quote globs so Stylelint expands them itself; node_modules is always ignored. Exit code 2 means lint problems, 1 a fatal error.

RUNNING

`stylelint "`*`<glob>`***`"`**
Lint files matching a glob

`stylelint` ***`<dir>`***`/`**
Lint a directory

`stylelint "`*`<glob>`***`" --allow-empty-input`**
No error if glob matches nothing

FIXING

`stylelint --fix "`*`<glob>`***`"`**
Fix what is auto-fixable

SEVERITY AND EXIT CODES

`stylelint -q "`*`<glob>`***`"`**
Show errors only, hide warnings

`stylelint --max-warnings` ***`<n>`***
Exit 2 above n warnings

Exit codes

Code	Meaning
`0`	No problems
`1`	Fatal error
`2`	Lint problems
`64`	Bad CLI usage
`78`	Invalid config file

OUTPUT

`stylelint -f` ***`<name>`***
Choose a formatter

`stylelint -f json "`*`<glob>`***`"`**
JSON report for tools

CACHE

`stylelint --cache "`*`<glob>`***`"`**
Only re-lint changed files

CACHE (cont.)

`stylelint --cache-strategy content`
Detect changes by content

CONFIG

`stylelint --config` ***`<file>`***
Use a specific config

`stylelint --print-config` ***`<file>`***
Print the resolved config

Config files searched (in order)

Where
`"stylelint" key in package.json`
`.stylelintrc`
`.stylelintrc.{cjs,mjs,js,ts,json,yaml,yml}`
`stylelint.config.{cjs,mjs,js,ts}`

.stylelintrc.json

```
{
  "extends": ["stylelint-config-
standard"],
  "rules": {
    "color-named": "never",
    "declaration-no-important": [true,
{ "severity": "warning" }],
    "selector-class-pattern": null
  },
  "ignoreFiles": ["dist/**"]
}
```

Per-file overrides

```
"overrides": [{
  "files": ["**/*.scss"],
  "customSyntax": "postcss-scss"
}]
```

`"rules": { "`*`<rule>`***`": null }`**
Turn a rule off

DISABLE COMMENTS

`/* stylelint-disable */ ... /* stylelint-enable */`
Turn off a region

`/* stylelint-disable` ***`<rule>`*** **`*/`**
Turn off one rule below

`/* stylelint-disable-next-line` ***`<rule>`*** **`*/`**
Skip the next line