Stylelint CSS linter

CONCEPTS

> Quote globs so Stylelint expands them itself; node_modules is always ignored. Exit code 2 means lint problems, 1 a fatal error.

RUNNING

`stylelint "<glob>"`
Lint files matching a glob

`stylelint <dir>/`
Lint a directory

`stylelint "<glob>" --allow-empty-input`
No error if glob matches nothing

FIXING

`stylelint --fix "<glob>"`
Fix what is auto-fixable

SEVERITY AND EXIT CODES

`stylelint -q "<glob>"`
Show errors only, hide warnings

`stylelint --max-warnings <n>`
Exit 2 above n warnings

Exit codes

Code	Meaning
0	No problems
1	Fatal error
2	Lint problems
64	Bad CLI usage
78	Invalid config file

OUTPUT

`stylelint -f <name>`
Choose a formatter

`stylelint -f json "<glob>"`
JSON report for tools

CACHE

`stylelint --cache "<glob>"`
Only re-lint changed files

CACHE (cont.)

`stylelint --cache-strategy content`
Detect changes by content

CONFIG

`stylelint --config <file>`
Use a specific config

`stylelint --print-config <file>`
Print the resolved config

Config files searched (in order)

Where
"stylelint" key in package.json
.stylelintrc
.stylelintrc.{cjs,mjs,js,ts,json,yaml,yml}
stylelint.config.{cjs,mjs,js,ts}

.stylelintrc.json

```
{
  "extends": ["stylelint-config-
standard"],
  "rules": {
    "color-named": "never",
    "declaration-no-important": [true,
{ "severity": "warning" }],
    "selector-class-pattern": null
  },
  "ignoreFiles": ["dist/**"]
}
```

Per-file overrides

```
"overrides": [{
  "files": ["**/*.scss"],
  "customSyntax": "postcss-scss"
}]
```

`"rules": { "<rule>": null }`
Turn a rule off

DISABLE COMMENTS

`/* stylelint-disable */ ... /* stylelint-enable */`
Turn off a region

`/* stylelint-disable <rule> */`
Turn off one rule below

`/* stylelint-disable-next-line <rule> */`
Skip the next line