Stylelint CSS linter

CONCEPTS

Quote globs so Stylelint expands them itself; node_modules is always ignored. Exit code 2 means lint problems, 1 a fatal error.

Config extends + rules
↓ applies to
Files CSS, SCSS, HTML…
↓ reports
Problems error or warning
↓ --fix
Fixed source safe rules only

RUNNING

`stylelint "<glob>"`
Lint files matching a glob

`stylelint <dir>/`
Lint a directory

`stylelint "<glob>" --allow-empty-input`
No error if glob matches nothing

`stylelint --stdin`
Read source from stdin

`stylelint --stdin-filename <name>`
Name the stdin input

`stylelint --custom-syntax <name>`
Use a custom PostCSS syntax

`stylelint --ignore-path <file>`
Read ignore patterns from a file

`stylelint --ignore-pattern "<glob>"`
Ignore extra paths

`stylelint --disable-default-ignores`
Also lint node_modules

FIXING

`stylelint --fix "<glob>"`
Fix what is auto-fixable

`stylelint --fix=lax "<glob>"`
Fix even with syntax errors

`stylelint --suppress "<glob>"`
Record current problems in a file

SEVERITY AND EXIT CODES

`stylelint -q "<glob>"`
Show errors only, hide warnings

`stylelint --max-warnings <n>`
Exit 2 above n warnings

Exit codes

Code	Meaning
0	No problems
1	Fatal error
2	Lint problems
64	Bad CLI usage
78	Invalid config file

OUTPUT

`stylelint -f <name>`
Choose a formatter

`stylelint -f verbose "<glob>"`
List files checked, with tally

`stylelint -f json "<glob>"`
JSON report for tools

`stylelint -o <path>`
Write the report to a file

`stylelint --custom-formatter <path>`
Use your own formatter module

CACHE

`stylelint --cache "<glob>"`
Only re-lint changed files

`stylelint --cache-location <path>`
Move the cache file or dir

`stylelint --cache-strategy content`
Detect changes by content

CONFIG

`stylelint --config <file>`
Use a specific config

`stylelint --print-config <file>`
Print the resolved config

Config files searched (in order)

Where
"stylelint" key in package.json
.stylelintrc
.stylelintrc.{cjs,mjs,js,ts,json,yaml,yml}
stylelint.config.{cjs,mjs,js,ts}

CONFIG (cont.)

.stylelintrc.json

```
{
  "extends": ["stylelint-config-standard"],
  "rules": {
    "color-named": "never",
    "declaration-no-important": [true, { "severity": "warning" }],
    "selector-class-pattern": null
  },
  "ignoreFiles": ["dist/**"]
}
```

Per-file overrides

```
"overrides": [{
  "files": ["**/*.scss"],
  "customSyntax": "postcss-scss"
}]
```

`"defaultSeverity": "warning"`
Make every rule a warning

`"rules": { "<rule>": null }`
Turn a rule off

DISABLE COMMENTS

`/* stylelint-disable */ ... /* stylelint-enable */`
Turn off a region

`/* stylelint-disable <rule> */`
Turn off one rule below

`/* stylelint-disable-next-line <rule> */`
Skip the next line

`/* stylelint-disable-line <rule> */`
Skip this line

`/* stylelint-disable <rule> -- <reason> */`
Add a description

`stylelint --report-needless-disables`
Flag useless disable comments

`stylelint --ignore-disables`
Ignore all disable comments

RECIPES

CI check

```
npx stylelint --cache --cache-strategy content \
  --max-warnings 0 "src/**/*.{css,scss}"
```