Supabase CLI Local stack and deploys

CONCEPTS

> The local stack runs in Docker containers: start Docker first, and expect the first start to pull images.

Local stack supabase start
↓ db diff
Migration supabase/migrations
↓ db push
Linked project remote database
↓ gen types
Typed client your app

> Most db and migration commands take --local (default), --linked or --db-url <url> to pick the target.

LOCAL STACK

supabase init
Create supabase/ config folder

supabase start
Start local Supabase containers

supabase status
Show URLs and keys of the local stack

supabase stop
Stop the local containers

LOGIN & LINK

supabase login
Log in with an access token

supabase login --token *<token>*
Log in non-interactively

supabase link --project-ref *<ref>*
Link folder to a hosted project

supabase projects list
List your projects

DATABASE

supabase db diff -f *<name>*
Write local schema changes as migration

supabase db diff --linked
Diff against the linked project

DATABASE (cont.)

supabase db push
Apply pending migrations to linked DB

supabase db push --dry-run
Show what would be pushed

supabase db pull
Fetch remote schema as a migration

supabase db reset
Recreate local DB from migrations and seed

supabase db dump -f *<file>*
Dump schema to a file

MIGRATIONS

supabase migration new *<name>*
Create an empty timestamped migration

supabase migration list
Compare local and remote migrations

supabase migration up
Apply pending migrations locally

EDGE FUNCTIONS

supabase functions new *<name>*
Scaffold a function

supabase functions serve
Serve functions locally

supabase functions deploy *<name>*
Deploy one function

SECRETS

supabase secrets set *<NAME>=<value>*
Set a function secret

TYPES & TESTS

supabase gen types --lang typescript --local
TypeScript types from local DB

supabase gen types --lang typescript --linked
TypeScript types from linked project