Supabase CLI Local stack and deploys

CONCEPTS

The local stack runs in Docker containers: start Docker first, and expect the first start to pull images.

Local stack supabase start
↓ db diff
Migration supabase/migrations
↓ db push
Linked project remote database
↓ gen types
Typed client your app

Most db and migration commands take --local (default), --linked or --db-url <url> to pick the target.

LOCAL STACK

`supabase init`
Create supabase/ config folder

`supabase start`
Start local Supabase containers

`supabase status`
Show URLs and keys of the local stack

`supabase stop`
Stop the local containers

LOGIN & LINK

`supabase login`
Log in with an access token

`supabase login --token <token>`
Log in non-interactively

`supabase link --project-ref <ref>`
Link folder to a hosted project

`supabase projects list`
List your projects

DATABASE

`supabase db diff -f <name>`
Write local schema changes as migration

`supabase db diff --linked`
Diff against the linked project

DATABASE (cont.)

`supabase db push`
Apply pending migrations to linked DB

`supabase db push --dry-run`
Show what would be pushed

`supabase db pull`
Fetch remote schema as a migration

`supabase db reset`
Recreate local DB from migrations and seed

`supabase db dump -f <file>`
Dump schema to a file

MIGRATIONS

`supabase migration new <name>`
Create an empty timestamped migration

`supabase migration list`
Compare local and remote migrations

`supabase migration up`
Apply pending migrations locally

EDGE FUNCTIONS

`supabase functions new <name>`
Scaffold a function

`supabase functions serve`
Serve functions locally

`supabase functions deploy <name>`
Deploy one function

SECRETS

`supabase secrets set <NAME>=<value>`
Set a function secret

TYPES & TESTS

`supabase gen types --lang typescript --local`
TypeScript types from local DB

`supabase gen types --lang typescript --linked`
TypeScript types from linked project