Syft Generate software SBOMs

CONCEPTS

Syft only lists what it can find in the source: packages and files, not vulnerabilities. Feed the SBOM to Grype or Trivy to scan it.

Source image, dir, archive, file
↓ catalogers
Syft finds packages
↓ -o format
SBOM SPDX, CycloneDX, JSON
↓ grype / attest
Scan or sign Grype, Trivy, Cosign

From source to SBOM

With no scheme, Syft tries the Docker daemon, then Podman, then containerd, then pulls from the registry. Pin it with --from or a scheme prefix.

Table is the default output but loses detail. The Syft JSON format (-o json) keeps everything and can be converted later.

SOURCES

syft *<image>*
Scan an image (daemon, else registry)

syft dir:*<path>*
Scan a directory

syft *<path>*
Directory, archive or SIF by path

syft registry:*<image>*
Pull from registry, skip the daemon

syft docker:*<image>*
Use the Docker daemon only

syft podman:*<image>*
Use the Podman daemon only

syft --from *<source>* *<target>*
Choose the source type explicitly

syft docker-archive:*<tar>*
Tarball from docker save

syft *<image>* **--platform** *<os/arch>*
Pick a platform of a multi-arch image

OUTPUT

syft *<src>* **-o json**
Syft JSON, all details

syft *<src>* **-o spdx-json**
SPDX as JSON

syft *<src>* **-o cyclonedx-json**
CycloneDX as JSON

syft *<src>* **-o** *<fmt>*=*<file>*
Write that format to a file

syft *<src>* **-o** *<fmt1>*=*<f1>* **-o** *<fmt2>*=*<f2>*
Several formats in one scan

SYFT_FORMAT_PRETTY=true
Indent JSON output

Without =<file> the SBOM goes to stdout; with it, nothing but logs. Handy: syft <src> -o json | jq ...

SCOPE AND FILTERING

syft *<image>* **--scope squashed**
Final filesystem only (default)

syft *<image>* **--scope all-layers**
Packages from every layer

syft *<src>* **--exclude '***<glob>***'**
Skip paths matching a glob

syft *<src>* **--exclude '**/node_modules/****'**
Ignore dependency folders

syft *<src>* **--select-catalogers** *<expr>*
Add or drop catalogers by name or tag

syft cataloger list
List available catalogers

CONVERT AND ATTEST

syft convert *<sbom>* **-o** *<fmt>*
Convert an SBOM to another format

syft convert *<sbom>* **-o** *<fmt>*=*<file>*
Convert into a file

syft attest -o *<fmt>* *<image>*
SBOM as in-toto attestation, keyless

CONVERT AND ATTEST (cont.)

syft attest --key cosign.key -o *<fmt>* *<image>*
Attest with a local key

Conversion is marked experimental and can lose data, because the formats do not hold the same fields. Keep the Syft JSON as the source of truth.

Attest accepts exactly one output format (syft-json, cyclonedx-json, spdx-json or spdx-tag-value) and only registry images.

CONFIG AND CLI

syft --version
Print the version

syft *<src>* **-v / -vv**
Verbose / debug logging

SYFT_*<OPTION>*=*<value>*
Set any option by environment variable

.syft.yaml
Config file in the working directory

Private registries use your Docker credentials (docker login) when Syft pulls with the registry source.

Install: brew install syft, or curl -sSfL https://get.anchore.io/syft | sudo sh -s -- -b /usr/local/bin

RECIPES

SBOM of an image, then scan it

```
syft <image> -o
json=sbom.syft.json
grype sbom:sbom.syft.json
```

Several formats from one scan

```
syft dir:. \
  -o spdx-json=sbom.spdx.json \
  -o cyclonedx-json=sbom.cdx.json
```

Everything in every layer, no test files

```
syft <image> --scope all-layers \
  --exclude '**/test/**' -o table
```