Syft Generate software SBOMs

CONCEPTS

Syft only lists what it can find in the source: packages and files, not vulnerabilities. Feed the SBOM to Grype or Trivy to scan it.

Source image, dir, archive, file
↓ `catalogers`
Syft finds packages
↓ `-o format`
SBOM SPDX, CycloneDX, JSON
↓ `grype / attest`
Scan or sign Grype, Trivy, Cosign
From source to SBOM

With no scheme, Syft tries the Docker daemon, then Podman, then containerd, then pulls from the registry. Pin it with --from or a scheme prefix.

Table is the default output but loses detail. The Syft JSON format (-o json) keeps everything and can be converted later.

SOURCES

`syft <image>`
Scan an image (daemon, else registry)

`syft dir:<path>`
Scan a directory

`syft <path>`
Directory, archive or SIF by path

`syft registry:<image>`
Pull from registry, skip the daemon

`syft docker:<image>`
Use the Docker daemon only

`syft --from <source> <target>`
Choose the source type explicitly

`syft docker-archive:<tar>`
Tarball from docker save

`syft <image> --platform <os/arch>`
Pick a platform of a multi-arch image

OUTPUT

`syft <src> -o json`
Syft JSON, all details

`syft <src> -o spdx-json`
SPDX as JSON

OUTPUT (cont.)

`syft <src> -o cyclonedx-json`
CycloneDX as JSON

`syft <src> -o <fmt>=<file>`
Write that format to a file

`syft <src> -o <fmt1>=<f1> -o <fmt2>=<f2>`
Several formats in one scan

SCOPE AND FILTERING

`syft <image> --scope squashed`
Final filesystem only (default)

`syft <image> --scope all-layers`
Packages from every layer

`syft <src> --exclude '<glob>'`
Skip paths matching a glob

`syft <src> --exclude '**/node_modules/**'`
Ignore dependency folders

`syft <src> --select-catalogers <expr>`
Add or drop catalogers by name or tag

CONVERT AND ATTEST

`syft convert <sbom> -o <fmt>`
Convert an SBOM to another format

`syft convert <sbom> -o <fmt>=<file>`
Convert into a file

`syft attest -o <fmt> <image>`
SBOM as in-toto attestation, keyless

`syft attest --key cosign.key -o <fmt> <image>`
Attest with a local key

Conversion is marked experimental and can lose data, because the formats do not hold the same fields. Keep the Syft JSON as the source of truth.

CONFIG AND CLI

`syft --version`
Print the version

`syft <src> -v / -vv`
Verbose / debug logging

`SYFT_<OPTION>=<value>`
Set any option by environment variable