# Task YAML task runner

**START HERE**

**`task --init`**
Create a Taskfile.yml

**`task --list`**
Show tasks with descriptions

**`task <name>`**
Run a task

**`task <a> <b>`**
Run several in order

**`task --dry <name>`**
Preview without running

**`task <name> -- <args>`**
Pass args as CLI_ARGS

**`task <name> <VAR>=<value>`**
Set a variable

**`task --watch <name>`**
Re-run on file changes

**task <name>** CLI call → **`deps`** **Dependencies** run first, in parallel → **`up-to-date?`** **Check** sources / status → **`cmds`** **Commands** run in order

## CONCEPTS

Running task with no name runs the task called default. Tasks live in Taskfile.yml, found by searching upwards from the current directory.

Variables are templated with {{.NAME}}; environment variables use $NAME in the shell.

Add .task/ to .gitignore: it stores the fingerprints used for up-to-date checks.

## RUNNING

**`task --list`**
List tasks that have a desc

**`task --list-all`**
List all tasks, even without desc

**`task <name>`**
Run a task

**`task --dry <name>`**
Print commands without executing

**`task --force <name>`**
Run even if up to date

**`task --parallel <a> <b>`**
Run the named tasks concurrently

**`task --summary <name>`**
Show the task's summary text

## RUNNING (cont.)

**`task --status <name>`**
Check up-to-date state, run nothing

**`task --watch <name>`**
Re-run when sources change

**`task --yes <name>`**
Answer yes to prompts

**`task --taskfile <file>`**
Use a different Taskfile

**`task --dir <path>`**
Run in and look for Taskfile in a directory

**`task --global <name>`**
Run from the Taskfile in $HOME

**`task --output group <name>`**
Group output per task

**`task --silent <name>`**
Do not echo commands

**`task --verbose <name>`**
Show detailed output

**`task --concurrency <n>`**
Limit concurrent tasks

**`task --failfast`**
Stop dependencies on first failure

**`task --list --json`**
Task info as JSON

**`task --init`**
Create a starter Taskfile.yml

## TASK BASICS

**`version: '3'`**
Required first line

**`tasks: <name>: cmds:`**
Define a task and its commands

**`cmd: <command>`**
Single command shorthand

**`desc: <text>`**
Text shown in --list

**`summary: <text>`**
Long text for --summary

**`aliases: [<alt>]`**
Alternative task names

**`dir: <path>`**
Working directory of the task

**`silent: true`**
Hide command echo

**`internal: true`**
Hide from CLI and --list

**`- task: <other>`**
Call another task as a command

**`ignore_error: true`**
Keep going if the command fails

**`timeout: 5m`**
Fail a command after a time limit

**`run: once`**
Run a dependency only once per call

**`default:`**
Task run by plain task

## DEPENDENCIES AND LOOPS

**`deps: [<a>, <b>]`**
Run these first, concurrently

**`deps: - task: <t> vars: {...}`**
Dependency with variables

**`for: [<a>, <b>] cmd: ... {{.ITEM}}`**
Loop a command over values

**`for: {var: <V>}`**
Loop over a variable's items

**`defer: <command>`**
Run cleanup when the task ends

**`platforms: [linux, darwin]`**
Limit task or command to platforms

## VARIABLES

**`vars: <NAME>: <value>`**
Define a variable

**`{{.NAME}}`**
Use a variable in a command

**`<NAME>: {sh: <command>}`**
Variable from command output

**`{{.NAME | default "x"}}`**
Fallback if unset

**`{{.CLI_ARGS}}`**
Everything after -- on the CLI

**`{{.TASK}}`**
Name of the running task

**`env: <NAME>: <value>`**
Export an environment variable

## VARIABLES (cont.)

**`dotenv: ['.env']`**
Load env vars from files

**`requires: vars: [<NAME>]`**
Fail if variable is missing

## UP-TO-DATE AND CHECKS

**`sources: ['**/*.go']`**
Files whose change triggers a run

**`generates: [<file>]`**
Files the task produces

**`method: checksum`**
Compare content (default)

**`status: [<test cmd>]`**
Skip when all commands exit 0

**`preconditions: - sh: <test> msg: <text>`**
Abort with a message if the test fails

**`prompt: <question>`**
Ask for confirmation first

## INCLUDES AND LAYOUT

**`includes: <ns>: <path>`**
Import tasks as ns:<task>

**`taskfile: <path>`**
Path in a long-form include

**`dir: <path> (include)`**
Working directory for included tasks

## INCLUDES AND LAYOUT (cont.)

**`task <ns>:<task>`**
Run a namespaced task

## RECIPES

**Build only when sources change**

```
tasks:
  build:
    desc: Build the binary
    sources: ['**/*.go',
go.mod]
    generates: [bin/app]
    cmds:
      - go build -o bin/app .
```

**Default task listing others**

```
tasks:
  default:
    cmds:
      - task --list
    silent: true
```

**Deploy with guard rails**

```
tasks:
  deploy:
    requires:
      vars:
        - name: ENV
          enum: [staging,
production]
    prompt: Deploy to {{.ENV}}?
    deps: [build]
    cmds:
      - ./deploy.sh {{.ENV}}
```

**Loop over directories**

```
tasks:
  test-all:
    cmds:
      - for: [api, web]
        cmd: cd {{.ITEM}} &&
npm test
```