Task YAML task runner

task <name> CLI call → **deps** **Dependencies** run first, in parallel → **up-to-date?** **Check** sources / status → **cmds** **Commands** run in order

CONCEPTS

Running task with no name runs the task called default. Tasks live in Taskfile.yml, found by searching upwards from the current directory.

Variables are templated with {{.NAME}}; environment variables use $NAME in the shell.

RUNNING

`task --list`
List tasks that have a desc

`task --list-all`
List all tasks, even without desc

`task <name>`
Run a task

`task --dry <name>`
Print commands without executing

`task --force <name>`
Run even if up to date

`task --parallel <a> <b>`
Run the named tasks concurrently

`task --summary <name>`
Show the task's summary text

RUNNING (cont.)

`task --watch <name>`
Re-run when sources change

`task --yes <name>`
Answer yes to prompts

`task --taskfile <file>`
Use a different Taskfile

`task --dir <path>`
Run in and look for Taskfile in a directory

`task --silent <name>`
Do not echo commands

`task --init`
Create a starter Taskfile.yml

TASK BASICS

`version: '3'`
Required first line

`tasks: <name>: cmds:`
Define a task and its commands

`cmd: <command>`
Single command shorthand

`desc: <text>`
Text shown in --list

`summary: <text>`
Long text for --summary

`aliases: [<alt>]`
Alternative task names

TASK BASICS (cont.)

`dir: <path>`
Working directory of the task

`silent: true`
Hide command echo

`- task: <other>`
Call another task as a command

`ignore_error: true`
Keep going if the command fails

`default:`
Task run by plain task

DEPENDENCIES AND LOOPS

`deps: [<a>, <b>]`
Run these first, concurrently

`deps: - task: <t> vars: {...}`
Dependency with variables

`for: [<a>, <b>] cmd: ... {{.ITEM}}`
Loop a command over values

`defer: <command>`
Run cleanup when the task ends

`platforms: [linux, darwin]`
Limit task or command to platforms

VARIABLES

`vars: <NAME>: <value>`
Define a variable

`{{.NAME}}`
Use a variable in a command

`<NAME>: {sh: <command>}`
Variable from command output

`{{.NAME | default "x"}}`
Fallback if unset

`{{.CLI_ARGS}}`
Everything after -- on the CLI

`{{.TASK}}`
Name of the running task

`env: <NAME>: <value>`
Export an environment variable

`dotenv: ['.env']`
Load env vars from files

`requires: vars: [<NAME>]`
Fail if variable is missing

UP-TO-DATE AND CHECKS

`sources: ['**/*.go']`
Files whose change triggers a run

`generates: [<file>]`
Files the task produces

UP-TO-DATE AND CHECKS (cont.)

`method: checksum`
Compare content (default)

`status: [<test cmd>]`
Skip when all commands exit 0

`preconditions: - sh: <test> msg: <text>`
Abort with a message if the test fails

`prompt: <question>`
Ask for confirmation first

INCLUDES AND LAYOUT

`includes: <ns>: <path>`
Import tasks as ns:<task>

`taskfile: <path>`
Path in a long-form include

`dir: <path> (include)`
Working directory for included tasks

`task <ns>:<task>`
Run a namespaced task

RECIPES

Default task listing others

```
tasks:
  default:
    cmds:
      - task --list
    silent: true
```