Tesseract OCR Text from images

START HERE

`tesseract <img> stdout`
OCR an image to the terminal

`tesseract <img> <out>`
Write <out>.txt

`tesseract <img> <out> -l <lang>`
Pick the language

`tesseract <img> <out> --psm 6`
Treat as one text block

`tesseract <img> <out> pdf`
Make a searchable PDF

`tesseract --list-langs`
Show installed languages

`tesseract <img> <out> tsv`
Words with boxes and confidence

`tesseract --version`
Show version and libraries

Image 300 dpi, clean, upright → `segment (--psm)` → **Layout** blocks, lines, words → `recognize (--oem, -l)` → **Text** words + confidence → `write (config names)` → **Output** txt, pdf, hocr, tsv

CONCEPTS

The call is tesseract <input> <outputbase> [options] [formats]. The output base gets its extension added; use stdout to print instead.

Options such as -l and --psm go before the output format names. Image quality (about 300 dpi, high contrast, straight) matters more than any flag.

BASICS

`tesseract <img> <out>`
OCR an image into <out>.txt

`tesseract <img> stdout`
Print recognized text

`tesseract stdin stdout`
Read image from a pipe, print text

`tesseract <list.txt> <out>`
OCR images listed one per line
All results are combined into one output per format.

`tesseract --version`
Show version

`tesseract --help`
Show usage

`tesseract --help-psm`
List page segmentation modes

`tesseract --help-oem`
List engine modes

LANGUAGES

`tesseract --list-langs`
List installed languages

`tesseract <img> <out> -l <lang>`
Recognize one language
Default is eng. Codes are three letters, e.g. deu, fra.

`tesseract <img> <out> -l <lang>+<lang>`
Combine several languages

`tesseract <img> <out> -l script/<Script>`
Use a script model

`tesseract --tessdata-dir <dir> --list-langs`
List languages in another folder

`TESSDATA_PREFIX=<dir> tesseract <img> <out>`
Point to the tessdata parent

A language needs its <lang>.traineddata file in the tessdata folder. Distros ship extras as separate packages.

LAYOUT (--PSM)

`tesseract <img> <out> --psm 3`
Fully automatic layout (default)

`tesseract <img> <out> --psm 6`
One uniform block of text

LAYOUT (--PSM) (cont.)

`tesseract <img> <out> --psm 7`
One single text line

`tesseract <img> <out> --psm 8`
One single word

`tesseract <img> <out> --psm 10`
One single character

`tesseract <img> <out> --psm 4`
One column of variable sizes

`tesseract <img> <out> --psm 11`
Sparse text, any order

`tesseract <img> <out> --psm 12`
Sparse text plus orientation

`tesseract <img> <out> --psm 0`
Detect orientation and script only

Wrong results on a tiny crop or a form field? Try 7, 8 or 6 before anything else. Use 11 for scattered labels.

ENGINE & TUNING

`tesseract <img> <out> --oem 1`
Use the LSTM neural engine

ENGINE & TUNING (cont.)

`tesseract <img> <out> --dpi <n>`
Set input resolution
Use when the image has no or a wrong dpi in its metadata.

`tesseract <img> <out> -c <name>=<value>`
Set a parameter

`-c tessedit_char_whitelist=0123456789`
Digits only

`-c preserve_interword_spaces=1`
Keep column spacing

`tesseract <img> <out> --user-words <file>`
Add a word list

`tesseract --print-parameters`
List all -c parameters

`OMP_THREAD_LIMIT=1 tesseract <img> <out>`
Limit to one thread
Faster for many small images run in parallel.

OUTPUT FORMATS

`tesseract <img> <out> txt`
Plain text, <out>.txt (default)

`tesseract <img> <out> pdf`
Searchable PDF with text layer

OUTPUT FORMATS (cont.)

`tesseract <img> <out> hocr`
hOCR HTML with word boxes

`tesseract <img> <out> tsv`
Tab-separated words, boxes, conf

`tesseract <img> <out> txt pdf hocr`
Write several formats at once

`tesseract <img> <out> quiet`
Suppress warnings and messages

tsv columns: level, page_num, block_num, par_num, line_num, word_num, left, top, width, height, conf, text. Filter low conf to find shaky words.

PREPARING IMAGES

`magick <in> -colorspace Gray <out>.png`
Convert to grayscale

`magick <in> -resize 200% <out>.png`
Enlarge small text

`magick <in> -density 300 <out>.png`
Set 300 dpi metadata

`magick <in> -threshold 50% <out>.png`
Binarize to black and white

PREPARING IMAGES (cont.)

`magick <in> -deskew 40% <out>.png`
Straighten a slightly tilted scan

`pdftoppm -r 300 -png <in>.pdf <prefix>`
Rasterize a PDF to pages
Tesseract reads images, not PDFs. pdftoppm is from poppler-utils.

Dark background or light text? Run -negate first. Tesseract wants dark text on a light background.

RECIPES

Searchable PDF from a scan

```
tesseract scan.png scan -l eng pdf
# writes scan.pdf with an invisible text layer
```

Scanned PDF to text

```
pdftoppm -r 300 -png doc.pdf page
ls page-*.png > pages.txt
tesseract pages.txt doc -l eng txt
```

Clean up, then OCR from a pipe

```
magick in.jpg -colorspace Gray -resize 200% png:- \
  | tesseract stdin stdout --psm 6
```

Confident words only

```
tesseract img.png stdout tsv \
  | awk -F'\t' '$1==5 && $11>80 {print $12}'
```