Tesseract OCR Text from images

CONCEPTS

The call is tesseract <input> <outputbase> [options] [formats]. The output base gets its extension added; use stdout to print instead.

Image 300 dpi, clean, upright
↓ `segment (--psm)`
Layout blocks, lines, words
↓ `recognize (--oem, -l)`
Text words + confidence
↓ `write (config names)`
Output txt, pdf, hocr, tsv

Options such as -l and --psm go before the output format names. Image quality (about 300 dpi, high contrast, straight) matters more than any flag.

BASICS

`tesseract <img> <out>`
OCR an image into <out>.txt

`tesseract <img> stdout`
Print recognized text

`tesseract stdin stdout`
Read image from a pipe, print text

`tesseract <list.txt> <out>`
OCR images listed one per line

`tesseract --version`
Show version

`tesseract --help`
Show usage

`tesseract --help-psm`
List page segmentation modes

`tesseract --help-oem`
List engine modes

LANGUAGES

`tesseract --list-langs`
List installed languages

`tesseract <img> <out> -l <lang>`
Recognize one language

`tesseract <img> <out> -l <lang>+<lang>`
Combine several languages

`tesseract --tessdata-dir <dir> --list-langs`
List languages in another folder

LANGUAGES (cont.)

`TESSDATA_PREFIX=<dir> tesseract <img> <out>`
Point to the tessdata parent

A language needs its <lang>.traineddata file in the tessdata folder. Distros ship extras as separate packages.

LAYOUT (--PSM)

`tesseract <img> <out> --psm 3`
Fully automatic layout (default)

`tesseract <img> <out> --psm 6`
One uniform block of text

`tesseract <img> <out> --psm 7`
One single text line

`tesseract <img> <out> --psm 8`
One single word

`tesseract <img> <out> --psm 10`
One single character

`tesseract <img> <out> --psm 4`
One column of variable sizes

`tesseract <img> <out> --psm 11`
Sparse text, any order

`tesseract <img> <out> --psm 0`
Detect orientation and script only

Wrong results on a tiny crop or a form field? Try 7, 8 or 6 before anything else. Use 11 for scattered labels.

ENGINE & TUNING

`tesseract <img> <out> --oem 1`
Use the LSTM neural engine

`tesseract <img> <out> --dpi <n>`
Set input resolution

`tesseract <img> <out> -c <name>=<value>`
Set a parameter

`-c tessedit_char_whitelist=0123456789`
Digits only

ENGINE & TUNING (cont.)

`-c preserve_interword_spaces=1`
Keep column spacing

OUTPUT FORMATS

`tesseract <img> <out> txt`
Plain text, <out>.txt (default)

`tesseract <img> <out> pdf`
Searchable PDF with text layer

`tesseract <img> <out> hocr`
hOCR HTML with word boxes

`tesseract <img> <out> tsv`
Tab-separated words, boxes, conf

`tesseract <img> <out> txt pdf hocr`
Write several formats at once

`tesseract <img> <out> quiet`
Suppress warnings and messages

tsv columns: level, page_num, block_num, par_num, line_num, word_num, left, top, width, height, conf, text. Filter low conf to find shaky words.

PREPARING IMAGES

`magick <in> -colorspace Gray <out>.png`
Convert to grayscale

`magick <in> -resize 200% <out>.png`
Enlarge small text

`magick <in> -density 300 <out>.png`
Set 300 dpi metadata

`magick <in> -threshold 50% <out>.png`
Binarize to black and white

`magick <in> -deskew 40% <out>.png`
Straighten a slightly tilted scan

`pdftoppm -r 300 -png <in>.pdf <prefix>`
Rasterize a PDF to pages

RECIPES

Searchable PDF from a scan

```
tesseract scan.png scan -l eng pdf
# writes scan.pdf with an invisible text layer
```