TFLint Terraform linter

START HERE

`tflint --init`
Install plugins

`tflint --enable-rule=<rule>`
Turn a rule on

`tflint`
Lint this directory

`tflint --fix`
Auto-fix issues

`tflint --recursive`
Lint every module dir

`tflint --chdir=<dir>`
Lint another dir

`tflint --format=compact`
One line per issue

`tflint --config=<file>`
Use a config file

.tflint.hcl plugins and rules → `tflint --init` → **Plugins** rulesets on disk → `tflint` → **Rules** run on your .tf files → `exit code` → **Issues** error / warning / notice

CONCEPTS

TFLint checks Terraform code for mistakes terraform validate misses: bad instance types, deprecated syntax, unused declarations.

The terraform ruleset is bundled and on by default; cloud rulesets (aws, azurerm, google) are plugins you must declare and install.

Run tflint from the module directory, or pass --chdir: it reads .tf files and config from there, not from parent dirs.

SETUP

`brew install terraform-linters/tap/tflint`
Install with Homebrew

`tflint --version`
Show version and loaded plugins

`tflint --init`
Install plugins from the config

`tflint --recursive --init`
Install plugins for all directories

`docker run --rm -v $(pwd):/data -t ghcr.io/terraform-linters/tflint`
Run the container image

SETUP (cont.)

`export GITHUB_TOKEN=<token>`
Avoid the --init rate limit
Unauthenticated --init is limited to 60 GitHub requests per hour per IP.

RUNNING

`tflint`
Lint the current directory

`tflint --chdir=<dir>`
Lint a different directory
Config is then read from <dir>/.tflint.hcl; path.cwd stays the original directory.

`tflint --recursive`
Lint each directory below here

`tflint --filter=<file>`
Only report issues in this file or glob

`tflint --fix`
Apply automatic fixes

`tflint --call-module-type=<all|local|none>`
Choose which module calls to inspect
Default is local; all also downloads remote modules.

`tflint --help`
List all options

OUTPUT AND EXIT CODES

`tflint --format=compact`
One line per issue

OUTPUT AND EXIT CODES (cont.)

`tflint --format=json`
Machine-readable output

`tflint --format=sarif`
SARIF for code scanning

`tflint --no-color`
Plain output

`tflint --force`
Exit 0 even if issues are found
Default exit codes: 0 clean, 1 error, 2 issues found.

`tflint --minimum-failure-severity=<error|warning|notice>`
Fail only at this severity or worse

Exit codes

Code	Meaning
0	No issues
1	Error while running
2	Issues found

RULES

`tflint --enable-rule=<rule>`
Enable a rule for this run

`tflint --disable-rule=<rule>`
Disable a rule for this run

`tflint --only=<rule>`
Run just this rule

RULES (cont.)

Rule priority, highest first

Source	Where
1. --only	CLI
2. --enable-rule / --disable-rule	CLI
3. rule blocks	Config file
4. preset	terraform plugin config
5. disabled_by_default	Config file

CONFIG FILE

`tflint --config=<file>`
Use this config file

`tflint --config=$(realpath .tflint.hcl) --recursive`
Share one config across directories
With --recursive, relative config paths resolve inside each directory.

Config lookup order

Order	File
1	`--config`
2	`$TFLINT_CONFIG_FILE`
3	`./.tflint.hcl`
4	`./.tflint.json`
5	`~/.tflint.hcl`
6	`~/.tflint.json`

CONFIG FILE (cont.)

plugin and rule blocks

```
plugin "aws" {
  enabled = true
  version = "0.4.0"
  source  = "github.com/
terraform-linters/tflint-
ruleset-aws"
}

rule
"terraform_typed_variables" {
  enabled = true
}
```

config block

```
config {
  format              =
"compact"
  call_module_type    = "local"
  disabled_by_default = false
  varfile             =
["dev.tfvars"]
  variables           =
["env=dev"]
}
```

Plugin version must be exact and without a leading v; constraints like >= 0.3 are not supported.

IGNORING ISSUES

Ignore one line

```
# tflint-ignore: <rule>
instance_type = "t1.2xlarge"
```

Ignore with a reason

```
# tflint-ignore: <rule> # too
new for TFLint
instance_type = "t1.2xlarge"
```

Ignore a whole file

```
# tflint-ignore-file: <rule>
```

IGNORING ISSUES (cont.)

tflint-ignore-file only works at the top of a file; inside a block it is an error. In .tf.json files use a "//" property.

MODULES AND VARIABLES

`tflint --var-file=<file>`
Load a tfvars file
*terraform.tfvars and *.auto.tfvars load automatically.*

`tflint --var='<name>=<value>'`
Set a variable

`tflint --ignore-module=<source>`
Skip a module by source
Use the module source, not its name in your code.

RECIPES

First run in a repo

```
cat > .tflint.hcl <<'EOF'
plugin "terraform" {
  enabled = true
  preset  = "recommended"
}
EOF
tflint --init
tflint --recursive
```

CI check with a report

```
tflint --init
tflint --recursive --
format=sarif > tflint.sarif
# exit code 2 fails the job
```