Trivy Security scanner

CONCEPTS

Pick the target type (image, fs, repo, config, k8s, sbom), then choose what to look for with --scanners.

Target image, fs, repo, k8s
↓ analyze
Scanners vuln, secret, misconfig, license
↓ match
Databases cached vuln DB and checks
↓ filter
Report table, json, sarif, SBOM

Defaults: image, fs and repo run vuln + secret; config runs misconfig only. License scanning is off unless requested.

The first run downloads the vulnerability DB into the cache; later runs reuse it, so offline CI needs a pre-warmed cache.

SCAN TARGETS

trivy image *<image>*
Scan an image (local daemon, then registry)

trivy image --input *<file.tar>*
Scan an image saved as tar

trivy fs *<dir>*
Scan a local project, incl. lock files

trivy repo *<path|url>*
Scan a local or remote git repo

trivy rootfs *<dir>*
Scan an extracted root filesystem

trivy sbom *<file>*
Scan an existing SBOM for vulns

trivy image --image-src *<list>*
Pick image sources, e.g. docker,podman

trivy image --platform *<os/arch>*
Scan a non-default platform

trivy registry login *<registry>*
Store registry credentials

SCANNERS

--scanners vuln
Only known vulnerabilities

--scanners vuln,secret,misconfig
Combine several scanners

--scanners misconfig
IaC and Dockerfile misconfigurations

--scanners secret
Hard-coded secrets only

--scanners license
Report package licenses

trivy config *<dir>*
Misconfig scan of Terraform, K8s, Helm, Dockerfile

FILTERING

--severity *<list>*
Keep only these severity levels

--ignore-unfixed
Skip vulns that have no fix yet

--ignore-status *<list>*
Hide statuses like affected,will_not_fix

.trivyignore
One finding ID per line; # comments

--ignorefile *<file>*
Use another ignore file (.trivyignore.yaml)

--skip-dirs *<glob>*
Do not scan matching directories

--skip-files *<glob>*
Do not scan matching files

OUTPUT AND CI

-f table
Human-readable table (default)

-f json -o *<file>*
Write JSON to a file

-f sarif -o *<file>*
SARIF for code-scanning tools

--exit-code *<n>*
Exit with n when issues are found

-q
Quiet: no progress bar or log noise

OUTPUT AND CI (cont.)

--no-progress
Hide the progress bar only

-d
Debug logging

SBOM

-f cyclonedx -o *<file>*
Generate a CycloneDX SBOM

-f spdx-json -o *<file>*
Generate an SPDX JSON SBOM

KUBERNETES

trivy k8s --report summary
Cluster overview (default report)

trivy k8s --report all
Detailed findings for the cluster

trivy k8s --scanners misconfig
Only misconfigurations in the cluster

--include-namespaces *<list>*
Limit to these namespaces

DATABASE AND CACHE

--skip-db-update
Use cached vuln DB, no download

--download-db-only
Fetch the DB, do not scan

--cache-dir *<dir>*
Move the cache (CI caching)

RECIPES

Gate a CI build on serious, fixable issues

```
trivy image --severity
HIGH,CRITICAL \
  --ignore-unfixed --exit-code 1
<image>
```

Project audit with a JSON report

```
trivy fs --scanners
vuln,secret,misconfig \
  -f json -o report.json .
```

Build an image and scan it before pushing

```
docker build -t <image> .
trivy image --exit-code 1 --
severity CRITICAL <image>
docker push <image>
```