tshark Packet analyzer CLI

START HERE

tshark -D
List interfaces

tshark -i *<iface>* **-c 20**
Capture 20 packets

tshark -i *<iface>* **-w** *<file.pcapng>*
Capture to a file

tshark -r *<file>*
Read a capture

tshark -r *<file>* **-Y** "*<filter>*"
Display filter

tshark -r *<file>* **-T fields -e** *<field>*
Extract fields

tshark -r *<file>* **-q -z conv,tcp**
Conversation stats

tshark -r *<file>* **-q -z follow,tcp,ascii,0**
Follow a stream

Capture -i, -f filter → (-w) **pcapng file** raw packets → (-r) **Display filter** -Y → (-T / -z) **Output** text, fields, JSON, stats

CONCEPTS

Only capture on networks and hosts you are authorised to monitor. Packet data can contain passwords and personal data; store and share captures with care.

Two filter languages: -f is a capture filter (BPF, same as tcpdump, applied while capturing); -Y is a display filter (Wireshark fields like ip.addr, applied after dissection).

Live capture usually needs root or the dumpcap capability; a trailing filter argument is a capture filter live, but a display filter with -r.

CAPTURE

tshark -D
List capture interfaces

tshark -i *<iface>*
Capture live on an interface

tshark -i *<iface>* **-c** *<n>*
Stop after n packets

tshark -i *<iface>* **-f** "*<filter>*"
Capture filter (BPF syntax)

CAPTURE (cont.)

tshark -i any
Capture on all interfaces
On Linux this uses cooked headers, so link-layer details are lost.

tshark -i *<iface>* **-s** *<len>*
Limit bytes kept per packet

FILES AND STOPPING

tshark -i *<iface>* **-w** *<file>*
Write raw packets to a file

tshark -r *<file>*
Read a capture file

tshark -i *<iface>* **-a duration:***<s>*
Stop after n seconds

tshark -i *<iface>* **-a filesize:***<kB>*
Stop at file size

tshark -i *<iface>* **-b filesize:***<kB>* **-b files:***<n>*
Ring buffer of files
Each -b takes one condition; repeat it for several.

tshark -i *<iface>* **-b duration:***<s>*
Start a new file every n seconds

tshark -r *<file>* **-w** *<out>* **-Y** "*<filter>*"
Save a filtered subset

DISPLAY FILTERS

-Y "ip.addr == *<ip>*"
Packets to or from a host

-Y "ip.src == *<ip>*"
Packets from a source

-Y "tcp.port == *<n>*"
TCP port, either side

-Y "udp.port == *<n>*"
UDP port, either side

-Y "http.request"
HTTP requests

-Y "http.request.method == \"POST\""
HTTP POST requests

-Y "dns.qry.name contains \"*<name>*\""
DNS queries by name

-Y "tcp.flags.syn == 1 && tcp.flags.ack == 0"
New TCP connections

-Y "tcp.analysis.retransmission"
Retransmitted segments

-Y "tcp.analysis.flags"
Any TCP problem flagged

-Y "tls.handshake.type == 1"
TLS Client Hello

-Y "*<a>* && !(*<b>*)"
Combine with and, or, not
Use && || ! or and or not; quote the whole expression.

DISPLAY FILTERS (cont.)

-Y "ip.addr == *<net>*/24"
Match a whole subnet

-Y "frame contains \"*<text>*\""
Search raw bytes for text

tshark -G fields
List all filter field names

OUTPUT

tshark -r *<file>* **-V**
Full packet detail

tshark -r *<file>* **-O** *<proto>*
Detail for one protocol only

tshark -r *<file>* **-x**
Hex and ASCII dump

tshark -r *<file>* **-n**
No name resolution

tshark -r *<file>* **-t ad**
Absolute date and time

tshark -r *<file>* **-T json**
Dump packets as JSON

tshark -r *<file>* **-q**
Suppress packet output

tshark -r *<file>* **-o** "*<pref>*:*<value>*"
Override a preference once

tshark -d tcp.port==*<n>*,*<proto>*
Decode a port as a protocol

OUTPUT (cont.)

tshark -o tls.keylog_file:*<file>*
Decrypt TLS with a key log
The key log comes from the client, e.g. a browser run with SSLKEYLOGFILE set.

EXTRACT FIELDS

tshark -r *<file>* **-T fields -e** *<field>*
Print chosen fields only

-T fields -e ip.src -e ip.dst -e tcp.dstport
Several fields, tab separated

-T fields -E header=y
Add a header row

-T fields -E separator=,
Comma separated output

-T fields -E occurrence=f
Keep first value of repeated fields

-T fields -e _ws.col.info
Include the Info column text

-T fields -e frame.time_epoch
Packet timestamp in epoch seconds

-T fields -e http.host -e http.request.uri
HTTP host and path

-T fields -e dns.qry.name
DNS names queried

EXTRACT FIELDS (cont.)

-T fields -e tls.handshake.extensions_server_name
TLS server names (SNI)

STATISTICS

tshark -r *<file>* **-q -z io,phs**
Protocol hierarchy

tshark -r *<file>* **-q -z conv,tcp**
TCP conversations

tshark -r *<file>* **-q -z endpoints,ip**
IP endpoints

tshark -r *<file>* **-q -z io,stat,***<s>*
Packets and bytes per interval

tshark -r *<file>* **-q -z expert**
Expert info summary

STREAMS AND OBJECTS

tshark -r *<file>* **-q -z follow,tcp,ascii,***<n>*
Follow TCP stream n as text

-Y "tcp.stream == *<n>*"
All packets of one TCP stream

tshark -r *<file>* **--export-objects http,***<dir>*
Save files from HTTP traffic