Velero Kubernetes backup

CONCEPTS

Velero stores backups as object-store tarballs; the CLI just creates Backup, Restore and Schedule objects the in-cluster server acts on.

velero CLI creates CRs
↓ Backup CR
Velero server deployment in velero ns
↓ upload
Object store BackupStorageLocation
↓ snapshot
Volumes VolumeSnapshotLocation

INSTALL

`velero install --provider <provider> --bucket <bucket> --secret-file <file> --plugins <image>`
Install server components

`velero install --no-secret`
Install using workload identity

`velero install --use-node-agent`
Enable file system backup

`velero version`
Show client and server version

BACKUPS

`velero backup create <name>`
Back up all namespaces

`velero backup create <name> --include-namespaces <ns>`
Back up chosen namespaces

`velero backup create <name> --selector <k>=<v>`
Back up by label

`velero backup create <name> --ttl <duration>`
Set retention (default 720h)

`velero backup create <name> --default-volumes-to-fs-backup`
Copy volume data with fs backup

BACKUPS (cont.)

`velero backup get`
List backups and status

`velero backup describe <name> --details`
Show contents and volume results

`velero backup logs <name>`
Show backup log

`velero backup delete <name>`
Delete backup and its data

RESTORES

`velero restore create --from-backup <name>`
Restore a backup

`velero restore create --from-backup <name> --include-namespaces <ns>`
Restore only some namespaces

`velero restore create --from-backup <name> --namespace-mappings <old>:<new>`
Restore into another namespace

`velero restore get`
List restores

`velero restore describe <name> --details`
Show warnings and errors

`velero restore logs <name>`
Show restore log

SCHEDULES

`velero schedule create <name> --schedule="<cron>"`
Create a recurring backup

`velero schedule get`
List schedules

STORAGE LOCATIONS

`velero backup-location get`
List locations and phase