Vitest Vite-native test runner

CONCEPTS

Plain vitest watches when run in a terminal and runs once when in CI or without a TTY. Use vitest run for a guaranteed single run.

RUN TESTS

npx vitest
Start watch mode (or one run in CI)

npx vitest run
Run once, no watch

npx vitest *<filter> <filter>*
Run files whose path contains a filter

npx vitest *<file>*:*<line>*
Run the test at a line number

npx vitest -t "*<pattern>***"**
Run tests whose full name matches a regexp

npx vitest run *<file>* **-t "***<pattern>***"**
Combine file and name filters

npx vitest related *<file>* **--run**
Run tests that import the given files

npx vitest run --changed
Run tests affected by uncommitted changes

WATCH MODE KEYS

a / Enter
Rerun all tests

f
Rerun only failed tests

u
Update failing snapshots

p
Filter by file name

t
Filter by test name regexp

q
Quit

OUTPUT

npx vitest run --reporter=verbose
One line per test

npx vitest run --reporter=json --outputFile=*<file>*
Write JSON results to a file

npx vitest run --reporter=junit --outputFile=*<file>*
JUnit XML for CI

npx vitest --ui
Open the browser dashboard

COVERAGE

npx vitest run --coverage
Run with coverage report

npx vitest run --coverage --coverage.reporter=html
Pick report formats

npx vitest run --coverage --coverage.include="src/"**
Count uncovered files too

npx vitest run --coverage --coverage.thresholds.lines=80
Fail below 80% lines

SNAPSHOTS AND FAILURES

npx vitest run -u
Rewrite all failing snapshots

npx vitest run --bail 1
Stop after the first failure

SPEED AND CI

npx vitest run --shard 1/3
Run one third of the suite

npx vitest run --project *<name>*
Run one workspace project

ENVIRONMENT AND DEBUGGING

npx vitest run --environment=jsdom
Test in a DOM environment