Vitest Vite-native test runner

CONCEPTS

> Plain vitest watches when run in a terminal and runs once when in CI or without a TTY. Use vitest run for a guaranteed single run.

RUN TESTS

`npx vitest`
Start watch mode (or one run in CI)

`npx vitest run`
Run once, no watch

`npx vitest <filter> <filter>`
Run files whose path contains a filter

`npx vitest <file>:<line>`
Run the test at a line number

`npx vitest -t "<pattern>"`
Run tests whose full name matches a regexp

`npx vitest run <file> -t "<pattern>"`
Combine file and name filters

`npx vitest related <file> --run`
Run tests that import the given files

`npx vitest run --changed`
Run tests affected by uncommitted changes

WATCH MODE KEYS

`a / Enter`
Rerun all tests

`f`
Rerun only failed tests

`u`
Update failing snapshots

`p`
Filter by file name

`t`
Filter by test name regexp

`q`
Quit

OUTPUT

`npx vitest run --reporter=verbose`
One line per test

`npx vitest run --reporter=json --outputFile=<file>`
Write JSON results to a file

`npx vitest run --reporter=junit --outputFile=<file>`
JUnit XML for CI

`npx vitest --ui`
Open the browser dashboard

COVERAGE

`npx vitest run --coverage`
Run with coverage report

`npx vitest run --coverage --coverage.reporter=html`
Pick report formats

`npx vitest run --coverage --coverage.include="src/**"`
Count uncovered files too

`npx vitest run --coverage --coverage.thresholds.lines=80`
Fail below 80% lines

SNAPSHOTS AND FAILURES

`npx vitest run -u`
Rewrite all failing snapshots

`npx vitest run --bail 1`
Stop after the first failure

SPEED AND CI

`npx vitest run --shard 1/3`
Run one third of the suite

`npx vitest run --project <name>`
Run one workspace project

ENVIRONMENT AND DEBUGGING

`npx vitest run --environment=jsdom`
Test in a DOM environment