Wrangler Cloudflare Workers CLI

START HERE

npm create cloudflare@latest
Scaffold a Worker

wrangler login
Sign in to Cloudflare

wrangler dev
Run locally

wrangler deploy
Publish to the edge

wrangler tail
Stream live logs

wrangler secret put *<KEY>*
Store a secret

wrangler d1 migrations apply *<db>*
Update the database

wrangler rollback
Undo a bad deploy

Code + config src/ and wrangler.jsonc → `wrangler dev` → **Local preview** localhost:8787 → `wrangler deploy` → **Cloudflare edge** live Worker → `wrangler tail` → **Live logs** debug and watch

CONCEPTS

Wrangler is the Workers CLI. Run it per project with npx wrangler (or pnpm/yarn) so the version matches the repo.

Bindings (KV, R2, D1) are declared in the config file and reach your code as env.<NAME>.

Most storage commands take --binding <name> or an ID, and --local or --remote to pick where they act.

ACCOUNT

wrangler login
Sign in through the browser

wrangler whoami
Show the signed-in account

wrangler logout
Remove stored credentials

PROJECT

npm create cloudflare@latest
Create a new Worker project

wrangler init [*<name>*]
Set up Wrangler in a folder

wrangler types
Generate types for your bindings
Writes worker-configuration.d.ts; rerun after config changes

DEVELOP

wrangler dev
Run the Worker locally

wrangler dev --port *<n>*
Use another local port

wrangler dev --remote
Run against remote resources

wrangler dev --local
Keep all bindings local

DEPLOY

wrangler deploy
Publish the Worker

wrangler deploy --env *<name>*
Deploy an environment

wrangler deploy --dry-run --outdir *<dir>*
Build without publishing

wrangler deploy --keep-vars
Keep dashboard-set variables

wrangler delete [*<name>*]
Remove a Worker

LOGS

wrangler tail
Stream live logs

wrangler tail --format pretty
Human-readable log lines

wrangler tail --status error
Only failed requests

wrangler tail --search *<text>*
Filter by log text

SECRETS

wrangler secret put *<KEY>*
Add or update a secret

wrangler secret list
List secret names

wrangler secret delete *<KEY>*
Remove a secret

wrangler secret bulk *<file>*
Set many secrets from JSON or .env

Local secrets go in .dev.vars (or .env); keep it out of git.

VERSIONS

wrangler versions upload
Upload without going live

wrangler versions list
List recent versions

wrangler versions deploy *<id>*@*<pct>*
Split traffic between versions

wrangler deployments list
Show deployment history

wrangler rollback [*<id>*]
Return to an earlier version
Without an id it goes back one version

KV

wrangler kv namespace create *<name>*
Create a namespace

wrangler kv namespace list
List namespaces

wrangler kv key put *<key>* *<value>* **--binding** *<b>*
Write a key

wrangler kv key get *<key>* **--binding** *<b>*
Read a key

wrangler kv key list --binding *<b>*
List keys

KV (cont.)

wrangler kv key delete *<key>* **--binding** *<b>*
Delete a key

wrangler kv bulk put *<file.json>* **--binding** *<b>*
Write many keys

R2

wrangler r2 bucket create *<name>*
Create a bucket

wrangler r2 bucket list
List buckets

wrangler r2 object put *<bucket>*/*<key>* **--file** *<path>*
Upload an object

wrangler r2 object get *<bucket>*/*<key>* **--file** *<path>*
Download an object

wrangler r2 object delete *<bucket>*/*<key>*
Delete an object

Object paths are <bucket>/<key>. Add --remote to act on the real bucket instead of local storage.

D1

wrangler d1 create *<name>*
Create a database

wrangler d1 list
List databases

wrangler d1 execute *<db>* **--command "**<sql>**"**
Run one SQL statement

wrangler d1 execute *<db>* **--file** *<file.sql>*
Run a SQL file

wrangler d1 migrations create *<db>* *<name>*
Add a migration file

wrangler d1 migrations apply *<db>*
Apply pending migrations

wrangler d1 migrations list *<db>*
Show unapplied migrations

wrangler d1 export *<db>* **--output** *<file.sql>*
Dump to a SQL file

wrangler d1 time-travel restore *<db>* **--timestamp** *<t>*
Restore to a past moment

D1 commands run locally unless you pass --remote; apply migrations locally first, then with --remote.

CONFIG

Config fields

Field	Purpose
`name`	Worker name
`main`	Entry file
`compatibility_date`	Runtime behaviour date
`compatibility_flags`	Opt-in runtime features
`vars`	Plain variables
`kv_namespaces`	KV bindings
`r2_buckets`	R2 bindings
`d1_databases`	D1 bindings
`routes`	Custom domains and routes
`assets`	Static asset directory
`observability`	Logs and traces
`env.<name>`	Per-environment overrides

Cloudflare recommends wrangler.jsonc for new projects; wrangler.toml still works.

vars and bindings are not inherited by [env.<name>]: repeat them in each environment.

Set compatibility_date to the day you start; bump it deliberately to adopt new runtime behaviour.

RECIPES

First deploy

```
npm create cloudflare@latest
my-app
cd my-app
npx wrangler dev
npx wrangler deploy
```

Database from scratch

```
npx wrangler d1 create <db>
npx wrangler d1 migrations
create <db> init
npx wrangler d1 migrations
apply <db> --local
npx wrangler d1 migrations
apply <db> --remote
```

Gradual rollout

```
npx wrangler versions upload
npx wrangler versions deploy
<new>@10% <old>@90% -y
# watch errors, then shift
traffic
npx wrangler versions deploy
<new>@100% -y
```

Add a secret and watch it work

```
npx wrangler secret put
API_TOKEN
npx wrangler tail --status
error
```