WSL Linux on Windows

START HERE

`wsl --install`
Install WSL + Ubuntu

`\\wsl.localhost\`*`<distro>`*
Linux files from Windows

`wsl -l -v`
Distros, state, version

`wsl --update`
Update WSL

`wsl`
Open default distro

`wsl -d` *`<distro>`*
Open another distro

`wsl --shutdown`
Stop everything

`explorer.exe .`
Open folder in Explorer

Windows host wsl.exe, .wslconfig
WSL 2 utility VM one Linux kernel
Distribution own rootfs, /etc/wsl.conf
Linux processes bash, apt, systemd

WSL 2: all distros share one lightweight VM

CONCEPTS

Commands are shown for PowerShell or CMD. From inside Linux, call the same tool as wsl.exe.

WSL 1 or WSL 2?

	WSL 1	WSL 2
Linux FS speed	slower	fast
/mnt/c speed	fast	slower
systemd, Docker	no	yes
LAN access	like Windows	NAT by default

INSTALL AND UPDATE

`wsl --install`
Install WSL and Ubuntu
Needs an admin prompt and usually a reboot.

`wsl --list --online`
Distros available to install
Short form: wsl -l -o.

`wsl --install -d` *`<distro>`*
Install a specific distro
Add --name <name> or --location <dir> to choose name and folder.

`wsl --update`
Update WSL to the latest release

`wsl --version`
Show WSL, kernel and WSLg versions

INSTALL AND UPDATE (cont.)

`wsl --status`
Show default distro and version

DISTRIBUTIONS

`wsl --list --verbose`
List distros with state and version
*Short form: wsl -l -v. The * marks the default.*

`wsl --list --running`
List running distros only

`wsl --set-default` *`<distro>`*
Make a distro the default
Short form: wsl -s <distro>.

`wsl --terminate` *`<distro>`*
Stop one distro
Short form: wsl -t <distro>.

`wsl --shutdown`
Stop all distros and the VM
Needed after editing .wslconfig or wsl.conf.

`wsl --set-version` *`<distro>`* **`2`**
Convert a distro to WSL 2
Can take long and fail on big distros: export a backup first.

`wsl --set-default-version 2`
Use WSL 2 for new installs

DISTRIBUTIONS (cont.)

`wsl --unregister` *`<distro>`*
Remove a distro and ALL its data
Deletes the root filesystem permanently; there is no undo.

`wsl --manage` *`<distro>`* **`--set-default-user`** *`<user>`*
Change the login user
The user must already exist in the distro.

RUN LINUX FROM WINDOWS

`wsl`
Shell in the default distro
Starts in the current Windows directory.

`wsl ~`
Shell in your Linux home

`wsl -d` *`<distro>`*
Shell in a specific distro

`wsl -u root`
Shell as root
Forgot the sudo password? Reset it here with passwd <user>.

`wsl` *`<command>`*
Run one Linux command
Uses the current directory; paths must be Linux paths.

RUN WINDOWS FROM LINUX

`explorer.exe .`
Open this folder in Explorer

`notepad.exe` *`<file>`*
Run any Windows program
Keep the .exe and the exact case of the name.

`cmd.exe /C` *`<command>`*
Run a CMD built-in like dir

FILES AND PATHS

`/mnt/c`
C: drive seen from Linux

`\\wsl.localhost\`*`<distro>`*
Distro's files seen from Windows
Older builds use \\wsl$\<distro>; enter \\wsl$ to list all distros.

`wslpath -w` *`<path>`*
Linux path to Windows path

`wslpath -u '`*`<C:\path>`*`'`
Windows path to Linux path
Quote it so the shell keeps the backslashes.

Speed
Keep projects in the Linux filesystem (~/project) when you work from Linux: /mnt/c is much slower under WSL 2.

BACKUP AND DISKS

`wsl --export` *`<distro>`* *`<file.tar>`*
Back up a distro to a tar file
Use - as the file name to write to stdout.

`wsl --import` *`<name>`* *`<dir>`* *`<file.tar>`*
Restore or clone as a new distro
No launcher for imports: set the user via [user] default.

CONFIGURATION

Two config files

	.wslconfig	/etc/wsl.conf
Where	%UserProfile%	inside each distro
Scope	global, WSL 2 VM	one distro
Sets	memory, CPUs, network	systemd, mounts, user

`[boot] systemd=true`
Run systemd in a distro (wsl.conf)

`[user] default=`*`<user>`*
Default login user (wsl.conf)

`[wsl2] memory=`*`<size>`*
Cap VM memory (.wslconfig)
Default is half of the Windows RAM. Sizes like 8GB or 512MB.

CONFIGURATION (cont.)

Changes apply only after the VM stops: run wsl --shutdown, or wait about 8 seconds after closing every shell.

NETWORKING

`localhost:`*`<port>`*
Reach a Linux server from Windows
Works by default (localhostForwarding).

`wsl hostname -I`
IP address of the WSL 2 VM
Capital -I; lower-case -i prints a placeholder address.

RECIPES

Back up and restore a distro

```
wsl --shutdown
wsl --export Ubuntu ubuntu.tar
# later, or on another PC:
wsl --import Ubuntu D:\wsl ubuntu.tar
```

Enable systemd (/etc/wsl.conf)

```
[boot]
systemd=true

[user]
default=<user>
# then run: wsl --shutdown
```